

AQUILINE METAL

F O O T S W I T C H



Engineered with an eagle eye on quality and value, the AQUILINE foot switch from Linemaster soars above the rest. With the choice of SPDT, DPDT, or two-stage operation, the patented AQUILINE is a versatile solution for applications requiring a precision lightweight to medium weight foot control. Available in momentary and maintained variations to fit the needs of any user. Form follows function in the AQUILINE's graceful curves and patented design, while a non-skid base pad and raised treadle ribs ensure positive performance. Of course you can always count on the famous consistency and familiar action you get with every Linemaster switch. Only from Linemaster - American made innovation at work.




LINEMASTER Switch Corporation
Tel (860) 974-1000

29 Plaine Hill Road, P.O. Box 238
Woodstock, Connecticut 06281-0238 USA
Fax (800) 974-FOOT(3668)

www.linemaster.com

FEATURES:

- Easy to Operate- Press and Hold on Actuation
- SPDT, DPDT, or Two-Stage Operation. Two-Stage Applications are only Available
- Available to IP68 Degree of Protection and CE Marked
- Available in Multi-Pedal Versions
- Non-Skid Base Pad and raised Ribs on Cover for Positive Traction during Operation
- Attractive Non-Glare Finish, Custom Colors, and Color Matching Available with Quantity Orders
- Integrated Adjustable Strain Relief Clamp
- Full and Oversized Guard Available



Approvals	EN 60529 Degree of Protection	Catalog Number	Description	Color	Circuit	Form	Electrical Ratings
	IP20	971-SM	Die Cast Zinc / Momentary	Black	SPDT	C	15A 125-250 VAC 1/2 H.P. 125 VAC
	IP20	972-S	Die Cast Zinc / Momentary 2-Stage	Black	SPDT Each Stage	C	
	IP20	974-SM	Die Cast Zinc / Momentary 2-Stage	Black	DPDT Each Stage	C	
	IP20	TWIN 971-SMC48 ¹	Die Cast Zinc / Momentary	Black	SPDT-Wired NO	A	13A 125-250 VAC; 1/2 H.P. 125-250 VAC
	IP20	971-DJM	Die Cast Zinc / MAINTAINED	Black	SPST-NO	A	12A 1 H.P. 250 VAC 1/2 H.P. 125 VAC
	IP20	971-DC3JM ²	Die Cast Zinc / MAINTAINED	Black	SPST-NO	A	
	IP20	971-DC36JM ³	Die Cast Zinc / MAINTAINED	Black	SPST-NO	A	
	IP20	971-DC38JM ⁴	Die Cast Zinc / MAINTAINED	Black	SPST-NO	A	

¹ Supplied with 8 ft. 16/4 cord without plug, green lead grounded. ² Supplied with 8 ft. 16/3 cord with 3 prong series plug (Restricts use of foot switch to 125 VAC only)
³ Supplied with 6 ft. 16/3 cord, grounded. ⁴ Supplied with 8 ft. 16/3 cord, grounded.